	8 7	6 5	4 3 1	
THE INFORM	ATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF , ANY REPRODUCTIONS IN PART OR WHOLE WITHOUT THE WRITTEN OF L-COM, INC. IS PROHIBITED.		REV DESCRIPTION	DATE CHANGED BY
PERMISSION	OF L-COM, INC. IS PROHIBITED.		A RELEASED FOR PRODUCTION	12/28/99 R.CARRICK
				05/08/02 MCCORMICK 07/15/02 MCCORMICK
			D ECN 5840: REVISED PIN NUMBERS, EXPLODED VIEW AND NEW FORMAT	11/18/11 D.FRISIELLO
		.90 [22.9]	- ^{8.0} _[203.2] → [17.4]	
		- - 08 [2.1]	_► .467 [11.86]	
		Ø.44		
	MD44FJF PIN 2			
	4 POSITION	45 [11.5]		
	MINIATURE CIRCULAR DIN		REMOVED FOR CLARITY.	
	WIRE CHARTDIN CONNECTORWIRE CODEPIN 1BLACKPIN 2WHITEPIN 3REDPIN 4GREEN		Since and the second seco	
	NOTES: 1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATE 2. THE D-FLAT ON THE THREADED BARREL OF ADAF	PTER		
	 MUST BE ALIGNED AS SHOWN ABOVE. 3. WIRE LEADS ARE 26AWG STRANDED TINNED CC WITH PVC INSULATION. 4. EIGHT INCH WIRES CUT BLUNT. 5. SILK SCREEN PART NUMBER AND COMPANY NA ON FACE SHOWN. 	OPPER ME USING BLACK INK		BEECHWOOD DR DRTH ANDOVER, N 01845
Ď	 REAR OF HOUSING TO BE POTTED. MATERIAL; SI CONFORMAL COATING. COLOR; BLACK 1/2-28 HEX NUT AND INTERNAL TOOTH WASHER COMPONENT ASSEMBLY SHALL BE TESTED FOR O COMPONENT ASSEMBLY SHALL BE INDIVIDUALLY ACCORDANCE WITH L-COM SPECIFICATION PS 	R INCLUDED. CONTINUITY. Y PACKAGED IN	OVERALL CABLE LENGTH TOLERANCE: \$12 [305] 560 [1524] = +125] / 0 >12 [305] 560 [1524] = +2[51] / 0 >60 [1524] = +2[51] / 0 >60 [1524] = +2[51] / 0 >60 [1524] = +2[51] / 0 >120 [3048] = 44 [102] / 0 >120 [3048] = 44 [102] / 0 >120 [3048] = 44 [102] / 0 >120 [3048] = 46 [152] - 0 >120 [3048] = 47 [102] / 0 AFC CATEGORY VIDEO ALL OTHER DIMENSIONAL TOLERANCES: XX = ±.02 XXX = ±.005 AFC 12/28/99 AFC PRODUCT DESCRIPTION MINI DIN 4 FEED THRU A UNDIMENSIONED FEATURES MAY VARY SIZE FISCM NO. 43321 DWG. NO. PROJECTION MAY OCCUR B 43321 MD44F	
			MAY OCCUR SCALE: 1:2 CAD FILE: MD44FJF.SLDDRW	SHEET 1 OF



